



## DECLARATION OF PERFORMANCE:

### THE CONSTRUCTION PRODUCTS (AMENDMENT ETC.) (EU EXIT) REGULATIONS 2020 NO 1359

This UK declaration of the performance from Knauf UK Ltd covers all essential characteristics required and specified by EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations



#### DOP NO. 0085\_DONN\_DX24\_KA-PT\_DX24-13\_2022\_10\_03\_DOP\_UKCA

1. Unique identification code of the product-type:

**Knauf Ceiling Solutions DONN DX24**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**DONN DX24**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Suspended ceiling substructure component for use internally in buildings**

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

**Knauf Ceiling Solutions GmbH & Co. KG, Elsenthal 15, 94481 Grafenau, Germany. Tel: +49 8552 4220**

5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Knauf UK Ltd, Kemsley Fields Business Park, Sittingbourne, Kent, ME9 8SR. Tel.: +441795-424499 Fax: +441795-428651 Email: info@knauf.co.uk**

6. System (AVCP) or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3 & 4**

**Notified Body/Bodies:** Holzforschung München (NB 0797) Reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**EN 13964:2014**

8. Declared Performance.

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire (R2F)	→ Appendix 1	EN 13964:2014
Release and/or content of dangerous substances	No release	EN 13964:2014
Loadbearing capacity	See technical data sheet	EN 13964:2014
- Load bearing performance - Dimensions and tolerances	→ Appendix 1 According to EN 13964:2014, Tab. 1	
Resistance to fixing	NPD	EN 13964:2014
Durability	→ Appendix 1	EN 13964:2014
These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use. Performance declared is for the system of which the product is a part of.		

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies.

#### Not Applicable

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



**Ian Stokes, Managing Director**  
Sittingbourne

Creation Date: 03/10/2022  
Revision Ref. 001  
Revision Date: 03/10/2022

**Build for the world we live in**

Appendix 1

	Reaction to fire		Load bearing performance			Durability
	Class	Test span (mm)	EI (Nm <sup>2</sup> )	admM (Nmm)		
DX24TS...	A1	1	1.200/1.000	350	7.000	B
DXB24TS...	A1	1	1.200/1.000	350	7.000	B
DX24XS...	A1	1	1.200/1.000	350	7.000	B
DXB24XS...	A1	1	500	350	7.000	B
DX24XS...KB/WK/MH	A1	1	1.000	350	17.000	D**
DX24TM...	A1	1	1.000	550	13.000	B
DXB24TM...	A1	1	1.000	550	13.000	B
DXB24XM...	A1	1	1.000	800	20.000	B
DX24XM...	A1	1	1.000	800	20.000	B
DX24XM...KB/WK/MH	A1	1	1.000	800	20.000	D**
DX24TH...	A1	1	1.800/1.000	1.100	14.000	B
DX24XH...	A1	1	1.800/1.000	1.250	16.000	B
DX24XH...KB/WK/MH	A1	1	1.800/1.000	1.250	16.000	D**
DC24XH...	A1	1	1.800/1.000	1.250	16.000	B
DX3-24XM...	A2-s1, d0	1	1.000/1.500	750	10.500	B
DX3-24TM...	A2-s1, d0	1	1.000/1.500	750	10.500	B
DX3B-24XM...	A2-s1, d0	1	1.000/1.500	750	10.500	B
DX324TH...	A2-s1, d0	1	1.000/1.800	1.100	15.000	B
DX3-24XH...	A2-s1, d0	1	1.000/1.800	1.100	15.000	B
VMDX3-24XH...	A2-s1, d0	1	1.000/1.800	1.100	15.000	B