



## DECLARATION OF PERFORMANCE:

### THE CONSTRUCTION PRODUCTS (AMENDMENT ETC.) (EU EXIT) REGULATIONS 2020 NO 1359

This UK declaration of the performance from Knauf UK Ltd covers all essential characteristics required and specified by EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations



#### DOP NO. 0085\_AQUAPANEL\_Exterior\_Basecoat\_White\_2022\_03\_22\_DOP\_UKCA

1. Unique identification code of the product-type:

**AQUAPANEL Exterior Basecoat White**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**AQUAPANEL Exterior Basecoat White**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Mineral basecoat for use on AQUAPANEL Cement board outdoor as substrate for renders**

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

**Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D – 58638 Iserlohn – Tel:+49 2374 5036-0, Fax: +49 5036-300, E-mail: aquapanel.info@knauf.com**

5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Knauf UK Ltd, Kemsley Fields Business Park, Sittingbourne, Kent, ME9 8SR. Tel.: +441795-424499 Fax: +441795-428651 Email: info@knauf.co.uk**

6. System (AVCP) or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**EN 998-1**

8. Declared Performance.

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	A1	EN 998-1:2003
Mortar Class	General purpose mortar (GP) for interior and exterior use (CS IV)	EN 998-1:2003
Water absorption	W2	EN 998-1:2003
Water vapour diffusion	$\mu = 5$ (Wet); $\mu + 20$ (dry cup) table value EN1745	EN 998-1:2003
Adhesion	$\geq 0.07$ N/mm <sup>2</sup> , FP: B	EN 998-1:2003
Thermal Conductivity ( $\lambda_{10,dry}$ )	$\leq 0.45$ W/Mk for P = 50%; $\leq 0.49$ W/Mk for P = 90% (Table value EN 1745, dry density $\leq 1400$ kg/m <sup>3</sup> )	EN 998-1:2003
Durability	NPD	EN 998-1:2003
These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use. Performance declared is for the system of which the product is a part of.		

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies.

#### Not Applicable

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Ian Stokes, Managing Director**  
Sittingbourne

Creation Date: 22/03/2022  
Revision Ref. 001  
Revision Date: 22/03/2022

**Build for the world we live in**

**AQUAPANEL®**