

DECLARATION OF PERFORMANCE:

THE CONSTRUCTION PRODUCTS (AMENDMENT ETC.) (EU EXIT) REGULATIONS 2020 NO 1359



This UK declaration of the performance from Knauf UK Ltd covers all essential characteristics required and specified by EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations

DOP NO. 0085_Coated_Channel_Connector_C3_2022_07_13_DOP_UKCA

1. Unique identification code of the product-type:

Knauf Coated Channel Connector C3

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Coated Channel Connector C3

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Suspended Ceiling substructure components, internally, to produce the substructure of an installed suspending ceiling.

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

Richter Systems GmbH & Co.KG, Flughafenstrabe 10, D-64347 Griesheim – Tel-+49 6155 876-33, E-Mail: Technik@richtersystems.com

5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Knauf UK Ltd, Kemsley Fields Business Park, Sittingbourne, Kent, ME9 8SR. Tel.: +441795-424499 Fax: +441795-428651 Email: info@knauf.co.uk

6. System (AVCP) or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 & 4

Notified Body/Bodies: MFPA Leizig GmbH, NB 0800 performed reaction to fire. - Third party tasks as set out in Annex V – Classification report no.3.1/13-403-3, classification A2-s1,d0, Corrosivity C3-long according to EN ISO 12944-6, report no. 5D 13 059_6 Forschungsinstitut fem, Schwabisch Gnund.

Initial type testing and factory production control performed by producer.

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 13964:2014

8. Declared Performance.

| Essential Characteristics | Performance | Harmonised Technical Specification |
|---------------------------|----------------------------------|------------------------------------|
| Reaction to Fire R2F | A2-s1,d0 | EN 13964:2014 |
| Load Bearing Capacity | See manufacturers documentation. | EN 13964:2014 |
| Durability | Class of corrosion C | EN 13964:2014 |
| Dangerous Substances - DS | NPD | EN 13964:2014 |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies.

Not Applicable

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ian Stokes, Managing Director Sittingbourne

Creation Date: 13/07/2022 Revision Ref. 001 Revision Date. 13/07/2022

Build for the world we live in