

Product Data Sheet Knauf Windliner Tape



Knauf Windliner Tape is a specialist tape with solvent free modified acrylic dispersion adhesive. It is designed for sealing joints and edges on the Knauf Windliner sheathing boards.

Areas of Application

Single-sided adhesive tape for exterior use, providing a high performing air and weather-tightness seal. Designed for sealing Knauf Windliner Sheathing boards.

Compliance Standards

EN 1939, EN 1849-2, EN 1372:2015 & EN 1373:2015

Key Benefits

- Quick and easy application
- Highly UV resistant
- Weather resistant
- Highly moisture resistant adhesive
- Excellent adhesive bond strength to Windliner Board substrates

Performance Data

Reaction to Fire (R2F)	Bonding Strength (N/25mm)	UV Resistance
Е	35 N/25 mm	6 months

Technical information

	D	imensions and Weigh	its	
Width (mm)	Length (m)	Colour	Weight (gsm)	Material Number
60	25	Black	330	525459
100	25	Black	330	610524

Creation Date: 08/06/2023 Revision Reference: 001 Revision Date: 08/06/2023

Build for the world we live in

www.knauf.co.uk



Storage and Handling

Store in shaded, dry conditions.

Packaging

Boxes.

Shelf Life

12 month-shelf life.

Disposal/Repair

Disposal should be in accordance with local authority requirements.

Health & Safety

Please refer to our Safety Data Sheet for guidance on Personal Protection Equipment required for the handling and installation of this product.

Application / Installation

- Surfaces must be dry and free of oil, grease, dust and other anti-adhesive components. Bonding to frozen surfaces is not possible.
- 2. Detach the release paper and affix the tape on the centre of the overlap of the two boards.
- 3. Gradually peel off the release paper and adhere the tape whilst keeping it tension-free and wrinkle-free to the substrate.
- 4. To consolidate the bond, apply firm pressure manually. Use of a seam roller will further improve the adhesion in most applications.

Exposed edges of cut to requirement boards are not required to be taped individually unless exposed to the elements. Taping is solely required for use to join the front face of the boards together or to relevant adjacent material to ensure water and weather tightness.

Additional Documentation

Safety Data Sheet

Knauf UK GmbH Company Accreditations:
bsi Quality Management Systems CERTIFIED

Customer Service

Technical Service

UK Tel: 0800 521 050 Eire Tel: 01 4620739 Email: cservice@knauf.com 0800 521050 (option 2) Live Webchat 09:00 -17:00 technical-uk@knauf.com Website www.knauf.co.uk

www.knauf.ie

Address

Knauf Kemsley Fields Business Park Sittingbourne Kent ME9 8SR

KML100490

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued. © Copyright Knauf 2023

Creation Date: 08/06/2023 Revision Reference: 001 Revision Date: 08/06/2023

Build for the world we live in