

Product Data Sheet

Knauf GIFAbond Blue Flooring Joint Adhesive



Knauf GIFAbond Blue Flooring Joint Adhesive is a single layer flooring edge adhesive for all Knauf Dry Screed Gypsum Floor Panels (GIFA FHB, Brio and Hugo).

Areas of Application

To be used on the tongue and groove edges of Knauf Gifa FHB and Hugo Floor Boards, as well as the lapped edge of Brio.

Compliance Standards

This product does not have a harmonised standard to allow for CE marking and or designated standard to allow for UKCA marking.

Key Benefits

- Quick and easy application
- Rated EMICODE® EC1 plus for very low emissions
- Does not contain diisocyanates
- Blue colour is easily identifiable
- Suitable for all Knauf dry screed floor panels

Technical Information

Dimensions and Weights			
Adhesive Colour	Weight (kg per bottle)	Approximate Coverage (m ² per bottle)	Material Number
Blue	1.2	1200x600mm Panels = 23	676976
		600x600mm Panels = 18	

Sustainability

Recyclability

The emptied bottle is fully recyclable.

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Volatile Organic Compound Content (VOC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no VOCs. For more information please consult the Safety Data Sheet.

Storage and Handling

Store between +15°C and +25°C in a dry area, protected from frost, high temperature and exposure to direct sunlight.

The working temperature is between +10°C and +30°C.

Packaging

Plastic bottle made from PE, supplied in a cardboard box on a wooden pallet.

Shelf Life

12 months.

Disposal

Disposal should be in accordance with local authority requirements.

European Waste Catalogue code: 08 04 10.

Health & Safety

Use of protective gloves and safety glasses is recommended. Avoid contact with skin. Refer to the safety data sheet for more information.

Application / Installation

Before application, make sure the panel edges are clear of dust.

When installing GIFA FHB and Hugo panels, apply a line of adhesive to the outer tongue and inner groove edge.

For Brio, apply 2 lines of adhesive, one tight to the shoulder and another line 10-15mm apart.

The adhesive has a 5 minute working time, with an approximate 24 hour curing time.

Scrape off excessive adhesive once dry and finish with Knauf Schnellgrund Floor Primer prior to bonding chosen flooring finish.

Additional Documentation

[Safety Data Sheet](#)



Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

0800 521050 (option 2)
Live Webchat 09:00 -17:00
technical-uk@knauf.com

Website

www.knauf.co.uk
www.knauf.ie

Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued.

© Copyright Knauf 2023