

Knauf Performance Plus

Data Sheet



Knauf Performance Plus, our highest specification plasterboard, has a high-density core with added performance-enhancing ingredients. The result is a board with extremely high levels of sound, moisture, fire and impact resistance, ideally suited to schools, hospitals and other large commercial projects.

Use with Knauf Performance Plus Screws.

Compliance: BS EN 520, Type A, D, F, H1, I and R.

Storage and Handling

Product must be stored flat, and be protected from inclement weather.

Appropriate personal protective clothing and equipment etc. should be used when handling all Knauf boards.

Manual handling guidelines should be adhered to at all times.

This board is unsuitable for areas that are continuously damp, humid or above 50°C.

Performance Data

In compliance with BS EN 520, the product is subject to initial type testing and continuous factory production control and bears the CE mark.

Technical Data

- Board weight and density:
12.5mm - 11.5kg/m² - 920kg/m³
15mm - 12.8kg/m² - 853kg/m³

For further product technical data, please refer to the Declaration of Performance.

Product Features

- Grey Face
- White Core
- Brown Reverse
- Board details printed on reverse
- Tapered Edge

Application / Installation

Use in accordance with BS 8000 British Standard Workmanship on building sites – Part 8: Code of practice for plasterboard partitions and dry linings.

Related Products

- Knauf Metal Sections
- Knauf Performance Plus Fixings*
- Knauf Sealant
- Knauf Intumescent and Acoustic Mastic
- Knauf Jointing Compounds, Tapes and Beads
- Knauf Deflection Head Fire Seal

* Collated versions also available. As Knauf Performance Plus is a high density board, it requires Knauf Performance Plus Fixings to be used.

Health & Safety

May irritate eyes or sensitive skin.

Dust may irritate respiratory system.

- Protective gloves, glasses and face mask are recommended.
- Avoid inhaling dust when cutting / handling product. Ventilate area and move person to fresh air.
- Avoid ingestion – wash mouth out immediately and drink plenty of water.
- Should any symptoms persist or allergic reaction occur, seek medical advice.

Refer to the product MSDS and DoP on:
www.knauf.co.uk

Please turn over for product material numbers, dimensions and pallet details.

Tapered Edge



Dimensions (mm)			Material No.	Pallet Details		
Thickness	Width	Length		Boards	m ²	Tonnes (Approx.)
12.5	1200	2400	400177	60	172.8	2.00
		3000	400185	48	172.8	2.00
15.0	1200	2400	400189	48	138.2	1.79
		3000	400195	36	129.6	1.67

Pallet weights exclude packaging.

Board weights and densities are for guidance purposes only and are subject to change.

Stated performance of plasterboard's are based on product characteristics and system testing using Knauf components.

For pricing details, please refer to the latest Knauf Price List.

KML100245

Customer Service

UK Tel: 0800 521 050

Eire Tel: 01 4620739

Email: cservice@knauf.co.uk

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Technical Support

Live Webchat 09:00–17:00

Email: technical@knauf.co.uk

Knauf
87 Broomhill Road
Tallaght
Dublin
D24

Literature

UK Tel: 03700 613 700

Eire Tel: +44 3700 613 700

Website

www.knauf.co.uk

www.knauf.ie



KnaufUK



@Knauf_UK



@Knauf_UK



Knauf UK & Ireland



KNAUF