

Easy Plaster Knauf UK & Ireland GmbH

Chemwatch: 5643-91 Version No: 2.1

Safety data sheet according to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Chemwatch Hazard Alert Code:

Issue Date: **20/11/2023**Print Date: **02/02/2024**L.REACH.GB.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

| Product name | Easy Plaster |
|-------------------------------|----------------|
| Chemical Name | Not Applicable |
| Synonyms | Not Available |
| Chemical formula | Not Applicable |
| Other means of identification | Not Available |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | A water-borne quick drying filler for the internal filling of most common building materials. Use according to manufacturer's directions. | |
|--------------------------|--|--|
| Uses advised against | No specific uses advised against are identified. | |

1.3. Details of the manufacturer or supplier of the safety data sheet

| Registered company name | Knauf UK & Ireland GmbH | |
|-------------------------|--|--|
| Address | emsley Fields Business Park Kent ME9 8SR Great Britain | |
| Telephone | 800 521 050 | |
| Fax | Not Available | |
| Website | ite www.knauf.co.uk | |
| Email | cservice@knauf.com | |

1.4. Emergency telephone number

| Association / Organisation | NHS Emergency Number |
|-----------------------------------|----------------------|
| Emergency telephone numbers | 111 |
| Other emergency telephone numbers | Not Available |

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

| Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 [1] |
|--|
|--|

Chemwatch: **5643-91**Version No: **2.1**

Page 2 of 13

Easy Plaster

Issue Date: **20/11/2023**Print Date: **02/02/2024**

2.2. Label elements

| Hazard pictogram(s) | Not Applicable |
|---------------------|----------------|
| | |
| Signal word | Not Applicable |

Hazard statement(s)

Not Applicable

Supplementary statement(s)

EUH208

Contains dipropylene glycol dibenzoate. May produce an allergic reaction.

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

| 1. CAS No 2.EC No 3.Index No 4.REACH No | %[weight] | Name | Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 | SCL / M-Factor | Nanoform Particle Characteristics |
|--|-----------|----------------------------------|---|-------------------|--------------------------------------|
| 1. 27138-31-4 2.248-258-5 3.Not Available 4.Not Available | <1 | dipropylene glycol dibenzoate | Sensitisation (Skin) Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 2; H317, H411 [1] | Not Available | Not Available |
| Legend: 1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567; 3. Classification drawn from C&L * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties | | | | | |

SECTION 4 First aid measures

4.1. Description of first aid measures

| Eye Contact | If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|--|
| Skin Contact | If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. |
| Inhalation | If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. |
| Ingestion | Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. |

Chemwatch: **5643-91**Version No: **2.1**

Page 3 of 13

Easy Plaster

Issue Date: **20/11/2023** Print Date: **02/02/2024**

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

- ► Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

5.2. Special hazards arising from the substrate or mixture

| Fire | Incom | patibility |
|------|----------|------------|
| riie | IIICOIII | patibility |

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may

5.3. Advice for firefighters

| 5.3. Advice for firefighters | | |
|------------------------------|---|--|
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. | |
| Fire/Explosion Hazard | Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit corrosive fumes. | |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

| ordination and material for contamination and creating ap | | |
|---|--|--|
| Minor Spills | Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up. Place spilled material in clean, dry, sealed container. Flush spill area with water. | |
| Major Spills | Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. | |

Issue Date: 20/11/2023 Print Date: 02/02/2024

- Wash area and prevent runoff into drains or waterways.
- ▶ If contamination of drains or waterways occurs, advise emergency services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

| 1.1. Precautions for safe | nandling |
|-------------------------------|---|
| Safe handling | Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. |
| Fire and explosion protection | See section 5 |
| Other information | Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. |

7.2. Conditions for safe storage, including any incompatibilities

| Suitable container | Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. |
|---|--|
| Storage incompatibility | Avoid reaction with oxidising agents |
| Hazard categories in accordance with Regulation (EC) No 1272/2008 | Not Available |
| Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of | Not Available |

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

| Ingredient | DNELs Exposure Pattern Worker | PNECs Compartment |
|----------------------------------|---|--|
| dipropylene glycol dibenzoate | Dermal 10 mg/kg bw/day (Systemic, Chronic) Inhalation 8.8 mg/m³ (Systemic, Chronic) Dermal 170 mg/kg bw/day (Systemic, Acute) Inhalation 35.08 mg/m³ (Systemic, Acute) Dermal 1.25 mg/kg bw/day (Systemic, Chronic) * | 0.02 mg/L (Water (Fresh)) 0.04 mg/L (Water - Intermittent release) 0.002 mg/L (Water (Marine)) 8.03 mg/kg sediment dw (Sediment (Fresh Water)) 0.803 mg/kg sediment dw (Sediment (Marine)) |

Issue Date: **20/11/2023**Print Date: **02/02/2024**

| Ingredient | DNELs Exposure Pattern Worker | PNECs Compartment |
|------------|---|--|
| | Inhalation 2.17 mg/m³ (Systemic, Chronic) * Oral 1.25 mg/kg bw/day (Systemic, Chronic) * Dermal 80 mg/kg bw/day (Systemic, Acute) * Inhalation 8.7 mg/m³ (Systemic, Acute) * Oral 80 mg/kg bw/day (Systemic, Acute) * | 1 mg/kg soil dw (Soil) 10 mg/L (STP) 333 mg/kg food (Oral) |

^{*} Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Not Available |

Not Applicable

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | TEEL-3 |
|--------------|---------------|---------------|---------------|
| Easy Plaster | Not Available | Not Available | Not Available |

| Ingredient | Original IDLH | Revised IDLH |
|----------------------------------|---------------|---------------|
| dipropylene glycol dibenzoate | Not Available | Not Available |

Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|----------------------------------|--|----------------------------------|
| dipropylene glycol dibenzoate | D | > 0.1 to ≤ 1 ppm |
| Notes: | Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health. | |

MATERIAL DATA

8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

8.2.1. Appropriate engineering controls

| Type of Contaminant: | Air Speed: |
|---|---------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air) | 0.25-0.5 m/s (50-100 f/min) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min) |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) |

Within each range the appropriate value depends on:

Issue Date: 20/11/2023 Print Date: 02/02/2024

| Lower end of the range | Upper end of the range |
|--|---------------------------------------|
| 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents |
| 2: Contaminants of low toxicity or of nuisance value only | 2: Contaminants of high toxicity |
| 3: Intermittent, low production. | 3: High production, heavy use |
| 4: Large hood or large air mass in motion | 4: Small hood - local control only |
| Simple theory shows that air velocity falls rapidly with distan generally decreases with the square of distance from the ex extraction point should be adjusted, accordingly, after refere | traction point (in simple cases). The |

extraction pipe. Velocity fore the air speed at the g source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used

8.2.2. Individual protection measures, such as personal protective equipment









Eye and face protection

Safety glasses with side shields.

- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eve irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
 - ▶ Wear safety footwear or safety gumboots, e.g. Rubber

Hands/feet protection

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Body protection

See Other protection below

Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.
- Skin cleansing cream.
- ▶ Eye wash unit.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|------------------------------------|--|-------------------------|-------------------------|
| up to 10 | 1000 | A-AUS / Class1 P2 | - |
| up to 50 | 1000 | - | A-AUS / Class 1 P2 |
| up to 50 | 5000 | Airline * | - |
| up to 100 | 5000 | - | A-2 P2 |
| up to 100 | 10000 | - | A-3 P2 |
| 100+ | | | Airline** |

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Latridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Issue Date: **20/11/2023**Print Date: **02/02/2024**

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | Paste; mixes with water. | | |
|--|--------------------------|---|----------------|
| | | | |
| Physical state | Non Slump Paste | Relative density (Water = 1) | 1.05-1.15 @20C |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | 8-9 | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | >100 | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water | Miscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |
| Nanoform Solubility | Not Available | Nanoform Particle Characteristics | Not Available |
| Particle Size | Not Available | | |

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

| 10.1.Reactivity | See section 7.2 |
|---|--|
| 10.2. Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| 10.3. Possibility of hazardous reactions | See section 7.2 |
| 10.4. Conditions to avoid | See section 7.2 |
| 10.5. Incompatible materials | See section 7.2 |
| 10.6. Hazardous decomposition products | See section 5.3 |

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or Ingestion toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives **Skin Contact** using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce Eye transient discomfort characterised by tearing or conjunctival redness (as with windburn). Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives Chronic using animal models); nevertheless exposure by all routes should be minimised as a matter of course. TOXICITY IRRITATION Easy Plaster Not Available Not Available **TOXICITY IRRITATION** dermal (rat) LD50: >2000 mg/kg[1] Eye: no adverse effect observed (not irritating)[1] dipropylene glycol dibenzoate Inhalation(Rat) LC50: >200 mg/l4h[2] Skin: no adverse effect observed (not irritating)[1] Oral (Rat) LD50: 3295 mg/kg^[1] Leaend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

DIPROPYLENE GLYCOL DIBENZOATE

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

The U.S. EPA High Production Volume Information System (HPVIS 2009) lists both diethylene glycol dibenzoate (DEGDB) and dipropylene glycol dibenzoate (DPGDB) as non-mutagenic and non-carcinogenic.

| Acute Toxicity | × | Carcinogenicity | × |
|-----------------------------------|---|--------------------------|---|
| Skin Irritation/Corrosion | × | Reproductivity | × |
| Serious Eye Damage/Irritation | × | STOT - Single Exposure | × |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × |
| Mutagenicity | × | Aspiration Hazard | × |

X - Data either not available or does not fill the criteria for classification Legend:

Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

Issue Date: 20/11/2023

Print Date: 02/02/2024

Issue Date: 20/11/2023 Print Date: 02/02/2024

| Easy Plaster Not | Endpoint | Test Duration (hr) | Species | Value | Source |
|----------------------------------|------------------|--------------------|---|------------------|------------------|
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| dipropylene glycol dibenzoate | Endpoint | Test Duration (hr) | Species | Value | Source |
| | LC50 | 96h | Fish | >3mg/l | 2 |
| | NOEC(ECx) | 96h | Fish | 1.2mg/l | 2 |
| Legend: | 4. US EPA, Ec | • | e ECHA Registered Substances - Ecotoxi lata 5. ECETOC Aquatic Hazard Assessn | | |

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air | |
|----------------------------------|-------------------------|------------------|--|
| dipropylene glycol dibenzoate | HIGH | HIGH | |

12.3. Bioaccumulative potential

| Ingredient | Bioaccumulation | | |
|----------------------------------|--------------------------|--|--|
| dipropylene glycol dibenzoate | MEDIUM (LogKOW = 4.0228) | | |

12.4. Mobility in soil

| Ingredient | Mobility |
|----------------------------------|------------------|
| dipropylene glycol dibenzoate | LOW (KOC = 1845) |

12.5. Results of PBT and vPvB assessment

| | P | В | T | | |
|-------------------------|-------------------------|---------------|--------|---------|--|
| Relevant available data | Not Available | Not Available | Not Av | ailable | |
| PBT | × | × | × | | |
| vPvB | × | x | × | | |
| PBT Criteria fulfilled? | PBT Criteria fulfilled? | | | | |
| vPvB | No | | | | |

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

| Product / Packaging disposal | Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Recycle containers if possible, or dispose of in an authorised landfill. |
|---------------------------------|---|
| Waste treatment options | Not Available |
| Sewage disposal options | Not Available |

SECTION 14 Transport information

Issue Date: 20/11/2023 Print Date: 02/02/2024

Labels Required

| Marine Pollutant | NO |
|------------------|----|

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

| 14.1. UN number or ID number | Not Applicable | Not Applicable | | | | |
|---------------------------------|-----------------------|----------------|----------------|--|--|--|
| 14.2. UN proper shipping name | Not Applicable | | | | | |
| 14.3. Transport hazard | Class | Not Appli | cable | | | |
| class(es) | Subsidiary Hazard | Not Appli | cable | | | |
| 14.4. Packing group | Not Applicable | | | | | |
| 14.5. Environmental hazard | Not Applicable | | | | | |
| | Hazard identification | (Kemler) | Not Applicable | | | |
| | Classification code | | Not Applicable | | | |
| 14.6. Special precautions | Hazard Label | Hazard Label | | | | |
| for user | Special provisions | | Not Applicable | | | |
| | Limited quantity | | Not Applicable | | | |
| | Tunnel Restriction C | ode | Not Applicable | | | |

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

| 14.1. UN number | Not Applicable | | | | |
|------------------------------------|---|-------------------|----------------|--|--|
| 14.2. UN proper shipping name | Not Applicable | | | | |
| | ICAO/IATA Class | Not Applicable | | | |
| 14.3. Transport hazard class(es) | ICAO / IATA Subsidiary Hazard | Not Applicable | | | |
| 0.000(00) | ERG Code | Not Applicable | | | |
| 14.4. Packing group | Not Applicable | | | | |
| 14.5. Environmental hazard | Not Applicable | | | | |
| | Special provisions | | Not Applicable | | |
| | Cargo Only Packing Instructions | | Not Applicable | | |
| | Cargo Only Maximum Qty / Pack | | Not Applicable | | |
| 14.6. Special precautions for user | Passenger and Cargo Packing Instructions | | Not Applicable | | |
| 101 4001 | Passenger and Cargo Maximum Qty / Pack | | Not Applicable | | |
| | Passenger and Cargo Limited Quantity Packing Instructions | | Not Applicable | | |
| | Passenger and Cargo Limited Ma | aximum Qty / Pack | Not Applicable | | |

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

| 14.1. UN number | Not Applicable | | | | |
|------------------------------------|-------------------------------|--|--|--|--|
| 14.2. UN proper shipping name | Not Applicable | Not Applicable | | | |
| 14.3. Transport hazard class(es) | IMDG Class IMDG Subsidiary Ha | IMDG Class Not Applicable IMDG Subsidiary Hazard Not Applicable | | | |
| 14.4. Packing group | Not Applicable | Not Applicable | | | |
| 14.5 Environmental hazard | Not Applicable | Not Applicable | | | |
| 14.6. Special precautions for user | EMS Number Special provisions | | | | |

Issue Date: 20/11/2023 Print Date: 02/02/2024

Limited Quantities

Not Applicable

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

| 14.1. UN number | Not Applicable | |
|------------------------------------|---------------------|----------------|
| 14.2. UN proper shipping name | Not Applicable | |
| 14.3. Transport hazard class(es) | Not Applicable Not | t Applicable |
| 14.4. Packing group | Not Applicable | |
| 14.5. Environmental hazard | Not Applicable | |
| 14.6. Special precautions for user | Classification code | Not Applicable |
| | Special provisions | Not Applicable |
| | Limited quantity | Not Applicable |
| | Equipment required | Not Applicable |
| | Fire cones number | Not Applicable |

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|----------------------------------|---------------|
| dipropylene glycol dibenzoate | Not Available |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|----------------------------------|---------------|
| dipropylene glycol dibenzoate | Not Available |

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

dipropylene glycol dibenzoate is found on the following regulatory lists

Not Applicable

Additional Regulatory Information

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

National Inventory Status

| National Inventory | Status |
|--|------------------------------------|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (dipropylene glycol dibenzoate) |

Chemwatch: **5643-91**Version No: **2.1**

Easy Plaster

Issue Date: **20/11/2023**Print Date: **02/02/2024**

| National Inventory | Status |
|----------------------------------|--|
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | Yes |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | Yes |
| Vietnam - NCI | Yes |
| Russia - FBEPH | Yes |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| Revision Date | 20/11/2023 |
|---------------|------------|
| Initial Date | 20/11/2023 |

Full text Risk and Hazard codes

| H317 | May cause an allergic skin reaction. |
|------|--|
| H411 | Toxic to aquatic life with long lasting effects. |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- $\ ^{\blacktriangleright}$ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ► IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ► ES: Exposure Standard
- ► OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ► BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ► DNEL: Derived No-Effect Level
- ► PNEC: Predicted no-effect concentration

Chemwatch: 5643-91 Page 13 of 13

Version No: 2.1 Easy Plaster

- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ► DSL: Domestic Substances List
- ► NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ► NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ► NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- ► INSQ: Inventario Nacional de Sustancias Químicas
- ► NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

| regulatio | ation according to n (EC) No 8 [CLP] and ents | Classification Procedure | |
|-----------|--|--------------------------|--|
| , EUH208 | 1 | Calculation method | |

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

Issue Date: 20/11/2023

Print Date: 02/02/2024